Atty. Dkt. No. 003493.00359 (ATT/2001-0335A)

→ PTO

## **IN THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) An apparatus A-method for managing a data network containing a data interface and a processor-connected to the data interface in order to receive objects, the objects containing traffic information, the apparatus method comprising:

## a data interface; and

a processor connected to the data interface in order to receive objects, the objects containing traffic information, the processor configured to perform the steps of:

- (a) receiving an object, wherein the object is characterized by at least one attribute and wherein the object comprises at least one data element;
- (b) determining whether to sample the object in accordance with a probabilistic parameter;
  - (c) sampling the object in response to step (b); and
  - (d) processing the sample in response to step (c).
- 2. (Currently Amended) The apparatus method of claim 1, wherein the probabilistic parameter is determined from a cost function.
- 3. (Currently Amended) The <u>apparatus</u> method of claim 2, wherein the cost function relates a network resource to a quality of measurements.
- 4. (Currently Amended) The <u>apparatus</u> method of claim 3, wherein the network resource corresponds to a sampling volume and the quality of measurements corresponds to a sampling accuracy.
- 5. (Currently Amended) The <u>apparatus</u> method of claim 1, wherein step (d) comprises:

Atty. Dkt. No. 003493.00359 (ATT/2001-0335A)

aggregating a plurality of samples in accordance with the at least one attribute.

- 6. (Currently Amended) The <u>apparatus</u> method of claim 1, wherein step (b) utilizes one of the at least one attribute to determine whether to sample the object.
- 7. (Currently Amended) The <u>apparatus</u> method of claim 6, wherein the one of the at least one attribute comprises a size of the object, wherein the size includes a contribution of the at least one data element.
- 8. (Currently Amended) The <u>apparatus</u> method of claim 7, wherein step (d) comprises:

normalizing the size of the object.

- 9. (Currently Amended) The <u>apparatus</u> method of claim 6, wherein the object comprises at least one data element, wherein the data element is selected from the group consisting of an octet, an Internet Protocol (IP) packet, a frame relay packet, and an Asynchronous Transfer Mode (ATM) cell.
- 10. (Currently Amended) The <u>apparatus</u> method of claim 1, <u>wherein the</u> <u>processor is further configured to perform</u> further comprising the steps of:
  - determining a measured usage of the data network in accordance with the at least one attribute; and
  - (f) charging a customer for the measured usage in accordance with a charging function, wherein the customer is associated with the at least one attribute and wherein the customer is presented a bill for a billing period and wherein a charging accuracy is related to the charging function and an accuracy of the measured usage.

Atty. Dkt. No. 003493.00359 (ATT/2001-0335A)

→ PT0

- 11. (Currently Amended) The <u>apparatus</u> method of claim 10, <u>wherein the</u> processor is further configured to perform further comprising the step of:
  - (g) adjusting the measured usage in order to control possible overcharging to the customer.
- 12. (Currently Amended) The <u>apparatus</u> method of claim 10, wherein step (f) utilizes a minimum usage and a usage charge.
- 13. (Currently Amended) The <u>apparatus</u> method of claim 12, wherein step (f) further utilizes a fixed charge.
- 14. (Currently Amended) The <u>apparatus</u> method of claim 10, <u>wherein the</u> processor is further configured to perform further comprising the step of:
  - (g) adjusting the probabilistic parameter in order to achieve a predetermined degree of accuracy of charging the customer, wherein a sampling volume is related to the probabilistic parameter.
- 15. (Currently Amended) The <u>apparatus</u> method of claim 10, <u>wherein the</u> <u>processor is further configured to perform</u> further comprising the step of:
  - (g) adjusting the probabilistic parameter in order to reduce unbillable usage within a predetermined percentage of the measured usage, wherein a sampling volume is related to the probabilistic parameter.
- 16. (Currently Amended) The <u>apparatus</u> method of claim 10, <u>wherein the</u> <u>processor is further configured to perform</u> further comprising the step of:
  - (g) adjusting the billing period in order to control a degree of accuracy for charging the customer.
- 17. (Currently Amended) The <u>apparatus</u> method of claim 14, wherein the probabilistic parameter is adjusted.

Atty, Dkt. No. 003493.00359 (ATT/2001-0335A)

→ PTO

- 18. (Currently Amended) The apparatus method of claim 15, wherein the probabilistic parameter is adjusted.
- 19. (Currently Amended) The apparatus method of claim 16, wherein the probabilistic parameter is adjusted.
- 20. (Currently Amended) The apparatus method of claim 1, wherein the processor is further configured to perform further comprising the steps of:
  - obtaining at least one sample from step (d); and (e)
  - (f) calculating an estimated sampling volume from step (e).
- 21. (Currently Amended) The apparatus method of claim 20, wherein the processor is further configured to perform further comprising the step of:
  - storing the estimated sampling volume. (g)
- 22. (Currently Amended) The apparatus method of claim 20, wherein the processor is further configured to perform further-comprising the step of:
  - reconfiguring the data network in accordance with the estimated (g) sampling volume.
- 23. (Currently Amended) The apparatus method of claim 20, wherein the processor is further configured to perform further comprising the step of:
  - adjusting the probabilistic parameter in order that the measured (g) sampling volume approximates a targeted sampling volume.
- 24. (Currently Amended) The apparatus method of claim 23, wherein step (g) comprises:

updating a value of the probabilistic parameter corresponding to a sampling window.

Atty. Dkt. No. 003493.00359 (ATT/2001-0335A)

- 25. (Currently Amended) The apparatus method of claim 24, wherein a current value of the probabilistic parameter equals a previous value of the probabilistic parameter multiplied by N divided by M, wherein N equals the measured sampling volume and M equals to the targeted sampling volume and wherein the previous value corresponds to a previous sampling window.
- 26. (Currently Amended) The apparatus method of claim 24, wherein a current value of the probabilistic parameter equals a previous value of the probabilistic parameter multiplied by (N-R) divided by (M-R) if M is greater than N and multiplied by N/M if N is greater than M, wherein N equals the measured sampling volume, M equals the targeted sampling volume, and R equals the sampling volume for objects having a size greater than the previous value of the probabilistic parameter.
- 27. (Currently Amended) The apparatus method of claim 24, wherein a current value of the probabilistic parameter is determined by a set of numbers and a target sampling volume, wherein each number corresponds to a size of a sampled object that was sampled in a previous sampling window.
- 28. (Currently Amended) The apparatus method of claim 24, wherein the processor is further configured to perform further comprising the steps step of:
  - (h) immediately updating a value of the probabilistic parameter when the measured sampling volume is greater than the targeted sampling volume in proportion to a measurement time duration, wherein the measurement time duration is less than the sampling window.
- 29. (Currently Amended) The apparatus method of claim 28, wherein the processor is further configured to perform further comprising the step of:
  - realigning the sampling window in accordance with the step of (i) updating the value of the probabilistic parameter.

Atty. Dkt. No. 003493.00359 (ATT/2001-0335A)

→ PT0

- 30. (Currently Amended) The apparatus method of claim 25, wherein the processor is further configured to perform further comprising the step of:
  - adjusting the measured sampling volume in accordance with a (h) variance of the measured sampling volume.
- 31. (Currently Amended) The apparatus method of claim 26, wherein the processor is further configured to perform further comprising the step of:
  - adjusting the measured sampling volume in accordance with a variance of the measured sampling volume.
- 32. (Currently Amended) The apparatus method of claim 27, wherein the processor is further configured to perform further comprising the step of:
  - adjusting the measured sampling volume in accordance with a (h) variance of the measured sampling volume.
- 33. (Currently Amended) The apparatus method of claim 1, wherein step (c) utilizes a quasi-random data sampling algorithm.
- 34. (Currently Amended) The apparatus methed of claim 7, wherein the probabilistic parameter is associated with a probability function that is characterized by a value equal to zero when the size of the object is zero, a linearly increasing value when the size is between zero and the probabilistic parameter, and equal to one when the size is greater than the probabilistic parameter.
- 35. (Currently Amended) The apparatus method of claim 10, wherein the charging function comprises a fixed charge and a usage charge, wherein the usage charge is determined from a charge per unit of data, a minimum usage, and the measured usage.
- 36. (Currently Amended) The apparatus method of claim 1, wherein the probabilistic parameter corresponds to a first color and a second probabilistic parameter

→ PTO

PATENT

Atty. Dkt. No. 003493.00359 (ATT/2001-0335A)

corresponds to a second color, wherein each color is associated with the at least one attribute.

37. (Currently Amended) An apparatus A method for charging a customer for usage of a data network containing a data interface and a processor-connected to the data interface in order to receive objects, the objects containing traffic information, the apparatus method comprising:

a data interface; and

- a processor connected to the data interface in order to receive objects, the objects containing traffic information, the processor configured to perform the steps of:
- (a) adjusting a probabilistic parameter in accordance with a charging accuracy;
- (b) receiving an object, wherein the object is characterized by a size and a customer:
- (c) determining whether to sample the object in accordance with the probabilistic parameter, wherein the probabilistic parameter approximately optimizes a cost function and wherein the cost function relates the probabilistic parameter to a sampling accuracy and a sampling volume;
  - (d) sampling the object in response to step (c);
  - (e) normalizing the sample in response to step (d);
  - (f) determining the usage for the customer in accordance with step (e);
  - (g) adjusting the usage in accordance with the charging accuracy; and
  - (h) determining a charge to the customer in response to step (g).
- 38. (Currently Amended) An apparatus A method for managing a data network in accordance with a data volume, wherein the data network contains a data interface and a processor connected to the data interface in order to receive objects, the apparatus method comprising:

a data interface; and

a processor connected to the data interface in order to receive objects,

Atty. Dkt. No. 003493.00359 (ATT/2001-0335A)

the objects containing traffic information, the processor configured to perform the steps of:

- (a) adjusting a probabilistic parameter for a sampling window in accordance with a targeted sampling volume;
  - (b) receiving an object, wherein the object is characterized by a size;
- (c) determining whether to sample the object in accordance with the probabilistic parameter, wherein the probabilistic parameter approximately optimizes a cost function, wherein the cost function relates the probabilistic parameter to a sampling accuracy and a sampling volume;
  - (d) sampling the object in response to step (c);
  - (e) normalizing the sample in response to step (d);
- (f) determining an estimated traffic volume in accordance with step (e); and
  - (g) utilizing the estimated traffic volume to manage the data network.
- 39. (Original) A computer-readable medium containing instructions for controlling a computer system to manage a data network, by:

receiving an object, wherein the object is characterized by at least one attribute and wherein the object comprises at least one data element;

determining whether to sample the object in accordance with a probabilistic parameter;

sampling the object in response to determining whether to sample the object; and

processing the sample in response to sampling the object.

40. (Original) The computer-readable medium of claim 39, further containing instructions for controlling the computer system to manage the data network, by:

determining a measured usage of the data network in accordance with the at least one attribute: and

charging a customer for the measured usage in accordance with a charging function, wherein the customer is associated with the at least one

**図013/014** 

**PATENT** 

Atty. Dkt. No. 003493.00359 (ATT/2001-0335A)

attribute and wherein the customer is presented a bill for a billing period and wherein a charging accuracy is related to the charging function and an accuracy of the measured usage.

- 41. (Original) The computer-readable medium of claim 40, further containing instructions for controlling the computer system to manage the data network, by:
  - adjusting the measured usage in order to control possible overcharging to the customer.
- 42. (Original) The computer-readable medium of claim 40, further containing instructions for controlling the computer system to manage the data network, by:
  - adjusting the probabilistic parameter in order to reduce unbillable usage within a predetermined percentage of the measured usage, wherein a sampling volume is related to the probabilistic parameter.
- 43. (Original) The computer-readable medium of claim 40, further containing instructions for controlling the computer system to manage the data network, by:
  - adjusting the billing period in order to control a degree of accuracy for charging the customer.
- 44. (Original) The computer-readable medium of claim 39, further containing instructions for controlling the computer system to manage the data network, by:
  - obtaining at least one sample; and calculating an estimated sampling volume.